

SD HOUSING | SIDE-LOAD, BOLT-ON

Newly-Designed With Fluid Flow, Shock Absorption, Wear Life Upgrades And Pit Bull Features For Drilling With Your Favorite Directional Blade.



Using DigiTrak® Transmitters				Replacement Parts					
Drill Rig Thrust	Diameter	Thread (rear)	Bolt Pattern	Housing	Blade Bolts	Housing Lid	LidLock Pin	Lid Bolts	Pit Bull Dowel Pin
< 8,000 lb.	2.5"	FS200	VER 5, 3/8" bolts	5625-HT4-06	SHCS3/8X3/4	5625-HT4-CP	RP-038-175"	SHCS3/8X3/4	DP-050X075
6,000 - 10,000	2.5"	2" IF	VER 6, 1/2" bolts	5625-HT4-13	SHCS1/2X1	5625-HT4-CP	RP-038-175"	SHCS1/2X3/4	DP-075X075
10,000 - 20,000	2.75"	2" IF	VER 6, 1/2" bolts	5627-HT4-13	SHCS1/2X1	5627-HT4-CP	RP-038-175"	SHCS1/2X3/4	DP-075x100
20,000 - 40,000	3.25"	2.375" Reg	VER 6, 1/2" bolts	5632-HT4-13	SHCS1/2X1	5632-HT4-CP	RP-038-200"	SHCS1/2X3/4	DP-075x100

Using Subsite® Transmitters				Replacement Parts					
Drill Rig Thrust	Diameter	Thread (rear)	Bolt Pattern	Housing	Blade Bolts	Housing Lid	LidLock Pin	Lid Bolts	Pit Bull Dowel Pin
<10,000 lb.	2.5"	2" IF	DW 5, 12mm bolts	5925-HD4-14	SHCS12MMX25MM	5925-HD4-CP	RP-038-175"	SHCS12MMX20MM	DP-050X075
6,000 - 20,000	2.75"	2" IF	DW 5, 12mm bolts	5927-HD4-14	SHCS12MMX25MM	5927-HD4-CP	RP-038-175"	SHCS12MMX20MM	DP-050X075
20,000 - 30,000	3.25"	2.375" Reg	DW 6, 16mm bolts	5932-HD4-15	SHCS16MMX35MM	5932-HD4-CP	RP-038-200"	SHCS16MMX25MM	DP-075x100
20,000 - 40,000	3.50"	2.375" Reg	DW 6, 16mm bolts	5935-HD4-15	SHCS16MMX35MM	5935-HD4-CP	RP-038-200"	SHCS16MMX25MM	DP-075x100

SD HOUSING | SIDE-LOAD, THREAD-ON

Newly-Designed For DigiTrak® Transmitters And Subsite® Beacons And Use With Eagle Claw, Iron Fist, Bolt-On Bit Bodies, Or Your Favorite Hard Ground Bit.



Using DigiTrak® Transmitters				Replacement Parts				
Drill Rig Thrust	Diameter	Thread (rear)	Thread (front)	Housing	Bolt-On Bit Body	Housing Lid	LidLock Pin	Lid Bolt
6,000 - 10,000	2.5"	2" IF	2" IF	5625-HT4	5625-13	5625-HT4-CP	RP-038-175"	SHCS1/2X3/4
10,000 - 20,000	2.75"	2" IF	2" IF	5627-HT4	5627-13	5627-HT4-CP	RP-038-175"	SHCS1/2X3/4
20,000 - 40,000	3.25"	2.375" Reg	2.375" Reg	5632-HT4	5632-13	5632-HT4-CP	RP-038-200"	SHCS1/2X3/4

Using Subsite® Transmitters				Replacement Parts				
Drill Rig Thrust	Diameter	Thread (rear)	Thread (front)	Housing	Bolt-On Bit Body	Housing Lid	LidLock Pin	Lid Bolt
6,000 - 20,000	2.75"	2" IF	2" IF	5927-HD4	5927-14	5927-HD4-CP	RP-038-175"	SHCS12MMX20MM
20,000 - 30,000	3.25"	2.375" Reg	2.375" Reg	5932-HD4	5932-15	5932-HD4-CP	RP-038-200"	SHCS16MMX25MM
20,000 - 40,000	3.50"	2.375" Reg	2.375" Reg	5935-HD4	5935-15	5935-HD4-CP	RP-038-200"	SHCS16MMX25MM
40,000 - 80,0000	4.25"	2.875" IF	2.875" Reg	3742-HU3	1742-23	3742-HU3-CP	RP-038-200"	SHCS1/2X3/4